

Adhesive backing	Permanent
Country of origin	Product of China
Fade-resistance (indoor commercial window, pigment ink)	Not applicable
Fade-resistance (indoor home or office, pigment ink)	50 years away from direct sun using Original HP 83 UV Inks
Fade-resistance (outdoor, pigment ink)	Not applicable
Fade-resistance note (indoor commercial window)	Interior in-window display ratings by HP Image Permanence Lab on a range of HP media. HP predictions based on test data under Xenon-Arc illuminant—calculation assumes 6,000 Lux/12 hr day
Fade-resistance note (indoor home or office)	Display permanence rating for interior displays/away from direct sunlight, under glass by HP Image Permanence Lab and/or by Wilhelm Imaging Research, Inc. on a range of HP media. For details: http://www.hp.com/go/supplies/printpermanence .
Fade-resistance note (outdoor)	Display permanence rating according to test SAE J2527; in a vertical display orientation in simulated nominal outdoor display conditions for select high and low climates, including exposure to direct sunlight and water; performance may vary as environmental conditions change. Permanence Lab. For details: http://www.hp.com/go/supplies/printpermanence
Flame retardant	Not applicable
Manufacturer Warranty	HP offers a range of self-adhesive materials with warranties that guarantee these products to be free of material or coating flaws and defects that affect the final use of the print and meet HP published specifications.
Media finish	Matte
Opacity	Greater than 96% per ISO 2471 Test Method
Package dimensions (W x D x H)	1630 x 135 x 135 mm
Package weight	7.6 kg
Primary material	Polypropylene
Print system value	HP printers, Original HP ink supplies, and Original HP printing materials are designed to work together as a system to provide uncompromising image quality, consistency, performance, durability, and value—every time.
Printing material brightness	Greater than 101 per ISO 2470 Test Method
Printing material dry time	2 minutes (@23°C, 50% RH)
Printing material lamination	Yes, cold
Printing material thickness	7.3 mil/185 microns (without liner), 8.9 mil/226 microns (with liner) per ISO 534 Test Method
Printing material waterfastness	Not applicable
Printing material weight (metric)	130 g/m ² per ISO 536 Test Method (without liner), 180 g/m ² per ISO 536 Test Method (with liner)
Product dimensions (W x D x H)	64.2 x 5.3 x 5.3 in
Roll dimensions (imperial)	60 in x 75 ft

Roll dimensions (metric)	1524 mm x 22.9 m
Shelf life	1 year, unopened in original packaging
Tear strength	1210N per ASTM D1004 Test Method
Tensile strength	10.3N per ASTM D882 Test Method
Thickness	7.3 mil/185 microns (without liner), 8.9 mil/226 microns (with liner) per ISO 534 Test Method
Unit Count	1
UPC number	884420179320
Warranty	HP offers a range of self-adhesive materials with warranties that guarantee these products to be free of material or coating flaws and defects that affect the final use of the print and meet HP published specifications.
Weight (Imperial)	13.2 lb
Weight (Metric)	6 kg
Whiteness	Greater than 119 per CIE Ganz 82 Test Method; greater than 111 per ISO 11475 Test Method

Extended specifications

Service Limitations	1 year, unopened in original packaging
----------------------------	--