

Overview & Specifications

Overview and features	
Overview	Whether you want to boost productivity or boost profitability, this cost-effective photo paper—optimized with HP pigment inks—delivers. See fast dry time and vibrant, long-lasting image quality with this high-quality, everyday recyclable[2] satin-finish paper.
Benefits	<ul style="list-style-type: none"> • Produce vibrant, long-lasting images • Boost productivity, enable enhanced profitability • Gain photo versatility and recyclability[2]
Target customers	Print service providers, graphic designers, professional photographers, digital fine art reproduction houses
Target applications	Photo Enlargements, Posters and Presentations, Trade Show and Event Displays, POP and Retail Displays
ICC profiles/Paper presets	
Front panel settings	http://www.hp.com/go/paperpresets
Printing specifications	
Roll dimensions	24 in x 100 ft
Media roll, core size	2 in
Brightness	90% per TAPPI T-452 Test Method and ISO 2470 Test Method
Metric page weight	235 g/m ² per ISO 536 Test Method
Opacity	96% per TAPPI T-425 Test Method and ISO 2471 Test Method
Whiteness	90 per ISO 11476 Test Method
Gloss level	Satin (60°) >20 per ASTM D-523 Test Method
Waterfastness	Water resistant with HP Vivid Photo inks, moderately water resistant with HP Photo inks and HP 83 UV inks. Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more information, see http://www.hp.com/go/supplies/printpermanence
Country of origin	Product of Germany
Primary material	Wood fiber and Polyethylene
Recycling Method	In North America and Asia (including Japan), recyclable in consumer collection systems that can accept mixed paper (may not be recyclable in your area); in Europe, recyclable in consumer collection systems that accept liquid packaging.
Image permanence	
Fade resistance	http://www.hp.com/go/supplies/printpermanence
Finishing/post processing	
Lamination	Yes, hot and cold
More information	http://www.hp.com/supplies/lamination
Operating conditions	
Operating temperature	60 to 85°F
Operating humidity	30 to 80% RH
Drying time	5 minutes (@ 23°C, 50% RH)
Shelf life	2 years, unopened in original packaging

Dimensions and weight	
Package weight	10.04 lb
Warranty	HP large format printing materials are free from defects in materials and workmanship. For warranty statement please see http://www.hp.com/go/HPMediaWarranties . To obtain warranty service, please contact HP customer support.
Footnotes	
	[1]Trademark license code FSC-C017543.
	[2]In North America and Asia (including Japan), recyclable in consumer collection systems that can accept mixed paper (may not be recyclable in your area); in Europe recyclable in consumer collection systems that accept liquid packaging.